

Model	ELRC70	ELRC130	ELRC170	ELRC220	ELRC340	ELRC510	ELRC930	ELRC1200 ELRC1500 ELRC1800	ELRC2500 ELRC3000 ELRC3500
Ultimate Pressure mbar @25°C Water	33								
Nomial Speed m³/h @ 50Hz @20°C water	60	105	135	180	285	425	775	1125-1750	2500-3000
Nominal Speed m³/h @ 60Hz @20°C water	70	130	170	220	340	510	930	1350-1750	2800-3500
Motor Speed rpm	1460 / 1800							880-1200	700-880
Power kW	4	4	5,5	7,5	11	15	30/37	45/55/75	75/90/110
Water Flow l/min	11	11	15	15	15	23	35	140/160	230/250/270
Inlet/Outlet Flange mm/in	38/1.5				51/2		79/3	6"/150	6"/150
Water Inlet NPT	1/2		3/4		1		1 1/4	2	2
Bareshaft Pump Est.Weight kg	70	90	105	115	165	185	365	1000	1600

Note: Stainless wheel, rust resistant axle, cast iron or carbon steel construction parts and stainless mechanical seals are standard for regular models. Chloride ion resistant Ni-Al-Copper alloy wheel and Teflon coated mechanical seal. are available. All models have full stainless steel option. Please note, the full stainless steel options have about 8% less suction speed comparing with its regular models.