

Model		Nominal Speed m ³ /h		Motor		Inlet/Outlet	Weight
Platform	Model	50Hz	at Max rpm	rpm	kW	mm/mm	KG
400	ER200	160	200	2900-3500	0,75	50/40	57
	ER400	320	400		1,5	80/50	66
	ER650	540	650		100/100	80	
890	ER890	740	890	2900-3500	3/4	100/100	134
	ER1300	1100	1300			150/150	160
EMBD	ERA900/EMBD540	750	900	2900-3500	4	100/100	121
	ERA1200/EMBD720	1000	1200				134
1600	ER1600	1450	1700	2900-3500	5,5	150/150	188
	ER3000	2160	2500		5.5/7.5		247
	ER3400	2400	2800			200/200	275
5300	ER3300	2750	3300	2900-3500	5.5/7.5/11	150/150	393
	ER5300	4400	5300		11/15/22	200/200	445
	ER7000	5900	7000			520	
9000	ER9000	6700	9000	1450-2000	11/15/18.5/22/30	250/250	1250
	ER13000	13000	15000	2900-3500	15/18.5/22	250/250	1250
12000	ER12000	9000	12000	1450-2000	18.5/22/30	350/350	1400
	ER19000	18000	21600	2900-3500	18.5/22	350/350	1400
30000	ER18000	14000	22000	1450-2200	18.5/22/30	500,350/350	1800
	ER30000	28000	33500	2900-3500	22/30/37		1800
	ER40000	33000	39000		22/30/37		2000
	ER45000	36900	44300		30/37	500/350	2200
	ER50000	44000	52800		37	630/450, 500/350	2600/3000

NOTES: OPTIONS: internal coating in PTFE, Ni-P, PFA, PEEK, Hastelloy. Mechanical seals with Kalrez or Solvay gaskets.